




19A0

六方小轮胎扳手

— 铬钒合金钢

— 镀铬



• Double end socket wrench for the hollow tube design, a long-type screw may be used.

Item	mm	D1 mm	D2 mm	L2 (mm)	L3 (mm)	L (mm)	g	
19A00607	6x7	10	11	5	6	105	44	30 / 180
19A00809	8x9	13	14	6	7	110	60	30 / 180
19A01011	10x11	15	16	7.5	8	120	79	24 / 144
19A01213	12x13	18	19	9	9.5	140	142	18 / 144
19A01415	14x15	20	22	10	11	145	138	12 / 96
19A01617	16x17	23	24	11	12	155	190	10 / 90
19A01819	18x19	25	26	13	15	165	243	8 / 72
19A02022	20x22	28	30	15	16	170	288	8 / 72

Item	 mm	D1 mm	D2 mm	L2 (mm)	L3 (mm)	L (mm)	 g	 / 
19A02123	21x23	29	31	15	17	185	318	6 / 54
19A02426	24x26	33	35	19	21	190	396	4 / 36
19A02528	25x28	34	37	19	21	205	511	4 / 24
19A02729	27x29	37	39	21	22	210	595	2 / 12
19A03032	30x32	40	42	22	26	210	671	2 / 12