

34522-DG



14x18单刻度双向更换式扭力扳手(牛顿米)

- 单刻度 - 牛顿米
- 使用更换头
- 质量符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 定位键设计可容易移除与安装
- 扭力公差 $\pm 3\%$ (正转)
- 顺时针 / 逆时针使用
- 扭力产品必须定期回公正单位做扭力校正以确保扭力值准确。建议的校正时间为使用一年或者是使用5,000次以上



Item	Size mm	Torque Range Nm	Incr.	Overall Length mm		
34522-1DG	14 x 18	20~100 N·m	0.5 N·m	430	1270	1 / 12
34522-2DG	14 x 18	40~200 N·m	1 N·m	485	1410	1 / 12
34522-3DG	14 x 18	60~340 N·m	2N·m	580	1590	1 / 12

Item	Size mm	Torque Range Nm	Incr.	Overall Length mm		
34522-4DG	14 x 18	100~600 N·m	5 N·m	1015	6200	1 / 2
34522-5DG	14 x 18	10~60 N·m	0.5 N·m	360	1270	1 / 12
34522-6DG	14 x 18	150~800 N·m	5 N·m	1195	6620	1 / 2
34522-7DG	14 x 18	70~350 N·m	2 N·m	580	1800	1 / 12
34522-8DG	14 x 18	200~1000 N·m	5 N·m	1200	6620	1 / 2
34522-9DG	14 x 18	80~400 N·m	2 N·m	580	1780	1 / 12