



34423-B



双刻度24齿扭力扳手(英吋磅 / 英呎磅 & 公斤米 / 公斤厘米)

- 双刻度 - 公斤厘米(或公斤米)与吋磅(或呎磅)
- 质量符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 4\%$ (正转)
- 顺时针 / 逆时针使用
- 扭力产品必须定期回公正单位做扭力校正以确保扭力值准确。建议的校正时间为使用一年或者是使用5,000次以上



Item	Square Drive	Torque Range in. lb / ft. lb.	Incr.	Torque Range kgf.cm kgf.m	Incr.	Overall Length mm		
34223-1B	1/4"	55~250 in·lb	1.5 in·lb	63~288 kgf·cm	1.13 kgf·cm	280	595	1 / 12
34323-1B	3/8"	55~250 in·lb	1.5 in·lb	63~288 kgf·cm	1.13 kgf·cm	280	595	1 / 12
34323-2B	3/8"	15~80 ft·lb	0.5 ft·lb	2.1~11.10 kgf·m	0.07 kgf·m	370	820	1 / 12
34423-1B	1/2"	30~150 ft·lb	1 ft·lb	4.2~20.8 kgf·m	0.14 kgf·m	450	1340	1 / 12
34423-2B	1/2"	50~250 ft·lb	2 ft·lb	6.9~34.6 kgf·m	0.27 kgf·m	570	2400	1 / 12