



34407-1A



数字扭力转接器

- 扭力公差： $\pm 2\%$
- 记忆：50 组
- 显示范围：0.1 牛顿米或呎磅；0.01 公斤米
- 操作模式：峰值 / 循迹
- 单位：公斤米, 呎磅, 牛顿米
- 电池：4号电池 x 2（不含电池）
- 电池寿命：110个小时
- 操作环境温度： -10°C - 60°C (13.9°F - 139.9°F)
- 保存环境温度： -20°C - 70°C (-4°F - 157.9°F)
- 操作环境相对湿气：15 to 90%
- 自动关机：待机70秒
- LED指示灯：绿, 红
- 超载警示125%：
 - 34207-1A: 37.5 牛顿米 (27.6 呎磅)
 - 34307-1A: 168.8 牛顿米 (124.5 呎磅)
 - 34407-1A: 250 牛顿米 (184.4 呎磅)
- 扭力产品必须定期回公正单位做扭力校正以确保扭力值准确。建议的校正时间为使用一年或者是使用5,000次以上





Item	Square Drive	Torque Range Nm	Torque Range ft · lb	Torque Range kgf·m	Size mm		
34207-1A-1	1/4"	6~30 N·m	4.4~22.1 ft·lb	0.61~3.06 kgf·m	L75 x W45 x H40	124	12 / 48
34307-1A-1	3/8"	27~135 N·m	19.9~99.6 ft·lb	2.75~13.76 kgf·m	L75 x W45 x H40	198	12 / 48
34407-1A-1	1/2"	40~200 N·m	29.5~147.5 ft·lb	4.08~20.38 kgf·m	L75 x W45 x H40	198.5	12 / 48