



## 34607-1A



### 数字扭力转接器

- 扭力公差： $\pm 2\%$
- 记忆：50 组
- 显示范围：0.1 牛顿米或呎磅；0.01 公斤米
- 操作模式：峰值 / 循迹
- 单位：公斤米, 呎磅, 牛顿米
- 电池：AA x 2 个（不含电池）
- 电池寿命：110 个小时
- 操作环境温度： $-10^{\circ}\text{C}$  -  $60^{\circ}\text{C}$  ( $13.9^{\circ}\text{F}$  -  $139.9^{\circ}\text{F}$ )
- 保存环境温度： $-20^{\circ}\text{C}$  -  $70^{\circ}\text{C}$  ( $-4^{\circ}\text{F}$  -  $157.9^{\circ}\text{F}$ )
- 操作环境相对湿气：15 to 90%
- 自动关机：待机70秒
- LED指示灯：绿, 红
- 超载警示125%：  
1,250 牛顿米 (922 呎磅)
- 扭力产品必须定期回公正单位做扭力校正以确  
保扭力值准确。建议的校正时间为使用一年或者  
是使用5,000次以上





| Item       | Square Drive | Torque Range<br>Nm | Torque Range<br>ft · lb | Torque Range<br>kgf·cm | Size<br>mm          |  |  |
|------------|--------------|--------------------|-------------------------|------------------------|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 34607-1A-1 | 3/4"         | 200~1000<br>N·m    | 147.6~738<br>ft·lb      | 20.4~102<br>kgf·m      | L110 x W56<br>x H60 | 585                                                                                 | 6 / 24                                                                              |