




1062



轻量化复合扳手(梅开扳手)

- 15°开口端在薄型外形在加厚设计
- 13°梅花端有薄壁与深孔设计
- 铬钒合金钢
- 依据DIN 3113 from A , ISO 7738



Item	Size mm	L (mm)		
1062-06	6	105	17	12 / 504
1062-07	7	115	19	12 / 504
1062-08	8	125	27	12 / 504

Item	Size mm	L (mm)		
1062-09	9	135	28	12 / 504
1062-10	10	145	36	12 / 504
1062-11	11	155	45	12 / 504
1062-12	12	165	58	12 / 216
1062-13	13	175	73	12 / 216
1062-14	14	185	88	12 / 216
1062-15	15	195	94	12 / 192
1062-16	16	205	108	12 / 192
1062-17	17	215	129	12 / 192
1062-18	18	225	151	12 / 144
1062-19	19	235	159	12 / 144
1062-20	20	245	186	12 / 144
1062-21	21	255	203	12 / 96
1062-22	22	265	221	12 / 96
1062-23	23	275	262	12 / 96
1062-24	24	285	281	6 / 54
1062-25	25	295	309	6 / 54
1062-26	26	305	343	6 / 54
1062-27	27	315	393	6 / 54
1062-28	28	325	416	6 / 48
1062-29	29	335	456	6 / 48

Item	Size mm	L (mm)		
1062-30	30	345	491	6 / 48
1062-32	32	365	573	6 / 48