

33461-100

Llave de Impacto Compuesta Para Trabajo Superpesado de 1/2" DR.

- Liviana 17%
- Control F/R (avance/retroceso) con una mano, interruptor avance/retroceso fácil
- Configuración de energía de 4 velocidades, velocidad completa en retroceso
- Mango TPR que puede ayudar a reducir el efecto de vibración en el operador
- Presión de aire: Recomendada 90 PSI
- Consumo promedio de aire: 207 L/min 7.3 CFM
- Sonido: 99.2 dBA
- Vibración: 13.32 m/s²



TPR ergonomic handle material reduces vibration



3-speed power setting, full speed in reverse



Item	Square drive inch	Square drive mm	Free Speed R.P.M	Max. Torque ft.lb	Max. Torque Nm	Overall Length (mm)	Overall Length (inch)	Air inlet inch	Net weight kgs	Net weight lbs	
33461-100	1/2"	12.7	9500	1000	1356	190	7.5	1/4" BSPT	2.30	5.28	1 / 8

Item	Square drive inch	Square drive mm	Free Speed R.P.M No	Max. Torque ft.lb	Max. Torque Nm	Overall Length (mm)	Overall Length (inch)	Air inlet inch	Net weight kgs	Net weight lbs	
33461-101	1/2"	12.7	9500	1000	1356	190	7.5	1/4" NPT	2.30	5.28	1 / 8