

# 34522-CG

## 14x18 Heavy Duty Interchangeable Torque Wrench (English & Newton Meter)

- Dual Scale - English & Newton Meter ( ft·lb & N·m )
- Using standard insert head
- Positive button design which removes the insert head easily
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±3%(CW )
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage










| Item | Size mm | Torque Range in. lb / ft. lb. | Incr. | Torque Range Nm | Incr. | Overall Length mm | g | |
|---|---|---|---|---|---|---|---|---|
| 34522-1CG | 14 x 18 | 15~80 ft·lb | 0.5 ft·lb | 23.7~105.1 N·m | 0.7 N·m | 430 | 1270 | 1 / 12 |
| 34522-2CG | 14 x 18 | 20~150 ft·lb | 1 ft·lb | 34~197 N·m | 1.4 N·m | 485 | 1410 | 1 / 12 |
| 34522-3CG | 14 x 18 | 50~250 ft·lb | 1 ft·lb | 75~332 N·m | 1.4 N·m | 580 | 1590 | 1 / 12 |