

34522-DG



14x18 Heavy Duty Interchangeable Torque Wrench (Newton Meter)

- Single scale - Newton Meter (N·m)
- Using standard insert head
- Positive button design which removes the insert head easily
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque $\pm 3\%$ (CW)
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage



Item	Size mm	Torque Range Nm	Incr.	Overall Length mm		
34522-1DG	14 x 18	20~100 N·m	0.5 N·m	430	1270	1 / 12
34522-2DG	14 x 18	40~200 N·m	1 N·m	485	1410	1 / 12

Item	Size mm	Torque Range Nm	Incr.	Overall Length mm		
34522-3DG	14 x 18	60~340 N·m	2N·m	580	1590	1 / 12
34522-4DG	14 x 18	100~600 N·m	5 N·m	1015	6200	1 / 2
34522-5DG	14 x 18	10~60 N·m	0.5 N·m	360	1270	1 / 12
34522-6DG	14 x 18	150~800 N·m	5 N·m	1195	6620	1 / 2
34522-7DG	14 x 18	70~350 N·m	2 N·m	580	1800	1 / 12
34522-8DG	14 x 18	200~1000 N·m	5 N·m	1200	6620	1 / 2
34522-9DG	14 x 18	80~400 N·m	2 N·m	580	1780	1 / 12