

# 34522-FG

## 14x18 Heavy Duty Interchangeable Torque Wrench (Newton Meter & English)

- Dual Scale - Newton Meter & English ( N·m & ft·lb )
- Using standard insert head
- Positive button design which removes the insert head easily
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±3%(CW )
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage











| Item | Size mm | Torque Range Nm | Incr. | Torque Range in. lb / ft. lb. | Incr. | Overall Length mm | g | |
|---|---|---|---|---|---|---|---|---|
| 34522-1FG | 14 x 18 | 20~100 N·m | 0.5 N·m | 16.6~71.9 ft·lb | 0.4 ft·lb | 430 | 1270 | 1 / 12 |
| 34522-2FG | 14 x 18 | 40~200 N·m | 1 N·m | 33.2~143.8 ft·lb | 0.8 ft·lb | 485 | 1410 | 1 / 12 |
| 34522-3FG | 14 x 18 | 60~340 N·m | 2 N·m | 51.6~243.4 ft·lb | 1.5 ft·lb | 580 | 1590 | 1 / 12 |