



34467-AG



Electronic Torque Wrench

- Electronic torque value readout
- Peak and trace mode selection
- Buzzer and LED indicator for presetting target torque
- Engineering units (N·m, ft·lb, in·lb, kgf·m) adjustment
- Switch off automatically after 60 seconds
- DIN ISO 6789:2017 & ASME B107.300-2010
- CW $\pm 2\%$ and CCW $\pm 3\%$ operation
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage
- Battery :AAA dry battery(Battery not included)

Display :
LCD display (± 2 digit) with measuring
ranges that can be selected for N·m, ft·lb,
in·lb, kg·m



LED warning light



Signal :
3-way signal when the maximum
torque value is reached, as a result
the wrench can be used in noisy
places.

• Electronic Torque Wrench (34367-2AG, 34467-1AG)



• Battery Cap:
- AAA x3 (Battery not included)
- Battery life 110 hrs



Item	Gear Teeth	Size inch		Nm	Torque ft·lb	Range in·lb	kg·m		 / 
34367-2AG-1	72	3/8"	460	27~135 N·m	19.9~99.6 ft·lb	239~1195 in·lb	2.75~13.76 kgf·m	1400	3/ 6
34467-1AG-1	36	1/2"	530	40~200 N·m	29.5~147.5 ft·lb	354~1770 in·lb	4.08~20.38 kgf·m	1500	3/ 6