

34423-A

Adjustable Torque Wrench (Newton Meter & Kilogram)

- Dual Scale - Newton Meter & Kilogram-force Centimeter / Kilogram-force meter (N·m & kgf·cm / kgf·m)
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±4%(CW)
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage











Item	Square Drive	Torque Range Nm	Incr.	Torque Range kgf.cm kgf.m	Incr.	Overall Length mm	g	
34223-1A	1/4"	5~25 N·m	0.1 N·m	51~255 kgf·cm	1 kgf·cm	280	595	1 / 12
34323-1A	3/8"	5~25 N·m	0.1 N·m	51~255 kgf·cm	1 kgf·cm	280	595	1 / 12
34323-2A	3/8"	20~110 N·m	1 N·m	2.04~11.22 kgf·m	0.1 kgf·m	370	820	1 / 12
34423-1A	1/2"	42~210 N·m	1 N·m	4.3~21.4 kgf·m	0.41 kgf·m	450	1340	1 / 12
34423-2A	1/2"	70~340 N·m	3 N·m	7.1~34.7 kgf·m	0.27 kgf·m	570	2400	1 / 12