

34423-C

Adjustable Torque Wrench (English & Newton Meter)

- Dual Scale - English & Newton Meter (in·lb, ft·lb, N·m)
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±4%(CW)
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage











Item	Square Drive	Torque Range in. lb / ft. lb.	Incr.	Torque Range Nm	Incr.	Overall Length mm	g	
34223-1C	1/4"	55~250 in·lb	1 in·lb	6.2~28.2 N·m	0.17 N·m	280	595	1 / 12
34323-1C	3/8"	55~250 in·lb	1 in·lb	6.2~28.2 N·m	0.17 N·m	280	595	1 / 12
34323-2C	3/8"	15~80 ft·lb	0.5 ft·lb	20.3~108.5 N·m	0.68 N·m	370	820	1 / 12
34423-1C	1/2"	30~150 ft·lb	1 ft·lb	40.7~203.4 N·m	1.35 N·m	450	1658	1 / 12
34423-2C	1/2"	50~250 ft·lb	2 ft·lb	67.8~339 N·m	2.71 N·m	570	2400	1 / 12