



3426E / 3436E / 3446E

3446E-HG


Classic type Professional Quality Adjustable Torque Wrench

- Dual Scale - English & Newton Meter (in·lb / ft·lb & N·m / kgf·m)
- Design for easy torque adjustment
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±4%(CW)
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage









Item	Size inch	Torque Range Nm	ft-lb	in-lb	kg.m	g	
3426E-1HG	1/4" 352	2.5~11 N·m	2~8 ft·lb	20~100 in·lb	0.3~1.2 kgf·m	630	1 / 12
3436E-1HG	3/8" 352	2.5~11 N·m	2~8 ft·lb	20~100 in·lb	0.3~1.2 kgf·m	740	1 / 12

Item	Size inch		Torque Range Nm	ft-lb	in-lb	kg.m	g	
3436E-2HG	3/8"	450	7~33 N·m	5~24 ft·lb	60~300 in·lb	0.7~3.4 kgf·m	870	1 / 12
3436E-3HG	3/8"	505	14~68 N·m	10~50 ft·lb	125~600 in·lb	1.4~7 kgf·m	1210	1 / 12
3446E-1HG	1/2"	555	25~135 N·m	20~100 ft·lb	200~1200 in·lb	3~14 kgf·m	1640	1 / 12
3446E-2HG	1/2"	590	50~225 N·m	40~160 ft·lb	400~2000 in·lb	5~23 kgf·m	1710	1 / 12
3446E-3HG	1/2"	803	70~330 N·m	50~250 ft·lb	600~3000 in·lb	7~35 kgf·m	3440	1 / 6