

3912M

Adjustable tap socket

- Designed for the assembly and removal of brake caliper screw connections on commercial vehicles
- Compatible with 1/4", 3/8", and 1/2" Drive tools; can be used with torque wrenches for precise tightening operations
- Features an adjustable tap handle with a chuck range of M3–M27, enabling quick tap changes, enhancing efficiency for taps, reamers, and screw extractors.
- Ideal for accurate tapping and threading in confined spaces









Item	Drive	S(mm) min.	S(mm) max.	Reference dimensions Tap (mm)	D1 mm	D2 mm	L (mm)	g	
39122008M	1/4	2.5	5.0	M3~M8	20.3	30.5	52.0	52	20 / 200
39123010M	3/8	2.0	6.0	M1~M10	23.0	34.5	53.0	221	4 / 64
39123012M	3/8	4.0	9.0	M5~M14	23.0	34.5	53.0	223	4 / 64
39124012M	1/2	6.0	12.0	M10~M20	25.3	38.5	53	265	4 / 64

Item	Drive	S(mm) min.	S(mm) max.	Reference dimensions Tap (mm)	D1 mm	D2 mm	L (mm)	g	
39124016M	1/2	12.0	17.0	M20~M27	34.0	48.3	55.5	280	1 / 48