




3445G



Heavy Duty Aluminum Adjustable Torque Wrench (Newton Meter & English)

- Dual Scale - English & Newton Meter (ft·lb & N·m)
- Industrial application
- Lightweight and robust; housing made by aluminium alloy
- Multi-lever mechanism brings length independence and accurate torque
- Loud click sound and string impulse when torque value reached
- Easy lock and adjustment design
- Tolerance of torque $\pm 3\%$ (CW)
- DIN ISO 6789:2017 & ASME B107.300-2010
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage



Item	Square Drive	Torque Range Nm	Incr.	Torque Range ft · lb	Incr.	Overall Length mm		
3445G-1FB	1/2"	40~200 N·m	5	30~150 ft·lb	5	563	1.50	1 / 12
3465G-1FB	3/4"	110~550 N·m	10	80~400 ft·lb	10	827	3.00	1 / 2
3465G-2FB	3/4"	140~760 N·m	10	100~560 ft·lb	10	827	3.00	1 / 2
3465G-3FB	3/4"	200~1000 N·m	10	140~740 ft·lb	10	1413	3.80	1 / 2
3485G-1DB	1"	600~1500 N·m	25	-	-	1615	10.90	1 / 1
3485G-2DB	1"	750~2000 N·m	50	-	-	2370	16.3	1 / 1