




4435M



1/2" DR. 6 Point Metric Deep Impact Socket

- 6 pt. hexagon impact socket
- Material - chrome molybdenum alloy steel
- Finishing - phosphate sunk
- 1/2" DR. deep version
- 6 points
- Metric size
- DIN 3121



Item	mm	D1 mm	D2 mm	mm	L (mm)	g	
443508M	8	15.0	24.8	12	78	124	6 / 120
443509M	9	16.3	24.8	12	78	137	6 / 120
443510M	10	17.6	24.8	12	80	149	6 / 120
443511M	11	18.8	24.8	13	80	153	6 / 120
443512M	12	20.0	24.8	14	80	164	6 / 120

Item	 mm	D1 mm	D2 mm	 mm	L (mm)		
443513M	13	21.2	24.8	14	80	169	6 / 120
443514M	14	22.5	24.8	14	80	168	6 / 120
443515M	15	23.8	29.8	16	80	225	6 / 96
443516M	16	25.0	29.8	16	80	233	6 / 96
443517M	17	26.2	29.8	16	80	239	6 / 96
443518M	18	27.5	29.8	17	80	246	6 / 96
443519M	19	28.8	29.8	18	80	254	6 / 96
443520M	20	29.0	29.8	20	80	244	6 / 96
443521M	21	29.8	29.8	20	80	247	6 / 96
443522M	22	32.4	30.0	22	80	278	5 / 60
443523M	23	33.2	30.0	24	80	316	5 / 60
443524M	24	34.4	30.0	24	80	297	5 / 60
443525M	25	36.0	30.0	24	80	326	5 / 60
443526M	26	37.0	30.0	27	80	367	5 / 60
443527M	27	38.0	30.0	27	80	364	5 / 60
443528M	28	40.0	30.0	27	80	424	5 / 50
443529M	29	40.0	30.0	27	80	407	5 / 50
443530M	30	42.0	30.5	30	80	422	5 / 50
443532M	32	46.0	30.0	32	80	503	1 / 24
443533M	33	46.0	30.0	32	80	471	1 / 24
443534M	34	46.0	30.0	33	80	466	1 / 24

Item	 mm	D1 mm	D2 mm	 mm	L (mm)	 g	 / 
443536M	36	47.0	30.0	36	80	445	1 / 24
443538M	38	50.0	30.0	38	80	515	1 / 24
443541M	41	56.0	30.0	38	80	689	1 / 24
443546M	46	64.0	30.0	40	80	943	1 / 24