

34462-CG

Heavy Duty Adjustable Torque Wrench (English & Newton Meter)

- Dual Scale - English & Newton Meter (in·lb, ft·lb, N·m)
- Design for easy torque adjustment
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque ±3%(CW)
- CW/CCW Direction
- Calibration must be done regularly to ensure accuracy. Suggested calibration period is at least every 12 months or 5000 times of usage









Item	Square Drive	Torque Range Nm	Incr.	Torque Range ft · lb	Incr.	Gear Teeth	Overall Length mm	g	
34262-1CG	1/4"	40~200 in·lb	1 in·lb	5.1~22.0 N·m	0.12 N·m	24	324	640	1/12

Item	Square Drive	Torque Range Nm	Incr.	Torque Range ft · lb	Incr.	Gear Teeth	Overall Length mm	g	
34362-1CG	3/8"	40~200 in·lb	1 in·lb	5.1~22.0 N·m	0.12 N·m	24	324	640	1/12
34362-2CG	3/8"	15~80 ft·lb	0.5 ft·lb	23.7~105 N·m	0.7 N·m	32	435	1300	1/12
34462-1CG	1/2"	20~150 ft·lb	1 ft·lb	34~197 N·m	1.4 N·m	32	521	1590	1/12
34462-2CG	1/2"	50~250 ft·lb	1 ft·lb	75~332 N·m	1.4 N·m	32	613	1810	1/12
34662-1CG	3/4"	100~450 ft·lb	5 ft·lb	169~576 N·m	6.8 N·m	24	1048	5500	1/2
34662-2CG	3/4"	100~600 ft·lb	5 ft·lb	169~779 N·m	6.8 N·m	24	1234	5600	1/2
34662-3CG	3/4"	150~750 ft·lb	5 ft·lb	237~983 N·m	6.8 N·m	24	1238	6150	1/2
34862-1CG	1"	150~750 ft·lb	5 ft·lb	237~983 N·m	6.8 N·m	24	1238	6150	1/2
34862-2CG	1"	200~1000 ft·lb	5 ft·lb	305~1322 N·m	6.8 N·m	24	1850	10510	1/2