



34462-DG



單刻度雙向快脫式扭力扳手(牛頓米)

- 單刻度 - 牛頓米
- 容易調整扭力
- 品質符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 3\%$ (正轉)
- 順時計 / 逆時計使用
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上



Item	Square Drive	Torque Range Nm	Incr.	Gear Teeth	Overall Length mm		
34262-2DG	1/4"	2~10 N·m	0.1 N·m	24	281	560	1 / 12
34262-1DG	1/4"	4~20 N·m	0.1 N·m	24	324	640	1 / 12
34262-3DG	1/4"	5~30 N·m	0.5 N·m	24	325	640	1 / 12
34362-1DG	3/8"	4~20 N·m	0.1 N·m	24	324	640	1 / 12

Item	Square Drive	Torque Range Nm	Incr.	Gear Teeth	Overall Length mm		
34362-3DG	3/8"	10~60 N·m	0.5 N·m	32	325	700	1 / 12
34362-2DG	3/8"	20~100 N·m	0.5 N·m	32	435	1300	1 / 12
34462-3DG	1/2"	20~100 N·m	1 N·m	32	436	1300	1 / 12
34462-1DG	1/2"	40~200 N·m	1N·m	32	521	1590	1 / 12
34462-2DG	1/2"	60~340 N·m	2 N·m	32	613	1810	1 / 12
34462-4DG	1/2"	80~400 N·m	2 N·m	32	613	1970	1 / 12
34662-1DG	3/4"	100~600 N·m	5 N·m	24	1048	5500	1 / 2
34662-2DG	3/4"	150~800 N·m	5 N·m	24	1234	5600	1 / 2
34662-3DG	3/4"	200~1000 N·m	5 N·m	24	1238	6150	1 / 2
34862-1DG	1"	200~1000 N·m	5 N·m	24	1238	6150	1 / 2
34862-2DG	1"	300~1500 N·m	10 N·m	24	1850	10510	1 / 2