



34423-A



雙刻度24齒扭力扳手(牛頓米 & 公斤米 / 公斤釐米)

- 雙刻度 - 牛頓米與公斤米(或公斤釐米)
- 品質符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 4\%$ (正轉)
- 順時計 / 逆時計使用
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上



Item	Square Drive	Torque Range Nm	Incr.	Torque Range kgf.cm kgf.m	Incr.	Overall Length mm		
34223-1A	1/4"	5~25 N·m	0.1 N·m	51~255 kgf·cm	1 kgf·cm	280	595	1 / 12
34323-1A	3/8"	5~25 N·m	0.1 N·m	51~255 kgf·cm	1 kgf·cm	280	595	1 / 12
34323-2A	3/8"	20~110 N·m	1 N·m	2.04~11.22 kgf·m	0.1 kgf·m	370	820	1 / 12
34423-1A	1/2"	42~210 N·m	1 N·m	4.3~21.4 kgf·m	0.41 kgf·m	450	1340	1 / 12
34423-2A	1/2"	70~340 N·m	3 N·m	7.1~34.7 kgf·m	0.27 kgf·m	570	2400	1 / 12