



34423-C



雙刻度24齒扭力扳手(英吋磅 / 英呎磅 & 牛頓米)

- 雙刻度 - 牛頓米與吋磅(或呎磅)
- 品質符合 DIN ISO 6789 & ASME B107.300-2010
- 扭力公差 $\pm 4\%$ (正轉)
- 順時計 / 逆時計使用
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上



Item	Square Drive	Torque Range in. lb / ft. lb.	Incr.	Torque Range Nm	Incr.	Overall Length mm		
34223-1C	1/4"	55~250 in·lb	1 in·lb	6.2~28.2 N·m	0.17 N·m	280	595	1 / 12
34323-1C	3/8"	55~250 in·lb	1 in·lb	6.2~28.2 N·m	0.17 N·m	280	595	1 / 12
34323-2C	3/8"	15~80 ft·lb	0.5 ft·lb	20.3~108.5 N·m	0.68 N·m	370	820	1 / 12
34423-1C	1/2"	30~150 ft·lb	1 ft·lb	40.7~203.4 N·m	1.35 N·m	450	1658	1 / 12
34423-2C	1/2"	50~250 ft·lb	2 ft·lb	67.8~339 N·m	2.71 N·m	570	2400	1 / 12