



34407-1A



數位扭力轉接器

- 扭力公差： $\pm 2\%$
- 記憶：50 組
- 顯示範圍：0.1牛頓米或呎磅；0.01公斤米
- 操作模式：峰值 / 循跡
- 單位：公斤米, 呎磅, 牛頓米
- 電池：4號電池 x 2（不含電池）
- 電池壽命：110個小時
- 操作環境溫度： -10°C - 60°C (13.9°F - 139.9°F)
- 保存環境溫度： -20°C - 70°C (-4°F - 157.9°F)
- 操作環境相對濕氣：15 to 90%
- 自動關機：待機70秒
- LED指示燈：綠, 紅
- 超載警示125%：
 - 34207-1A: 37.5 牛頓米 (27.6 呎磅)
 - 34307-1A: 168.8 牛頓米 (124.5 呎磅)
 - 34407-1A: 250 牛頓米 (184.4 呎磅)
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上





Item	Square Drive	Torque Range Nm	Torque Range ft · lb	Torque Range kgf·m	Size mm		
34207-1A-1	1/4"	6~30 N·m	4.4~22.1 ft·lb	0.61~3.06 kgf·m	L75 x W45 x H40	124	12 / 48
34307-1A-1	3/8"	27~135 N·m	19.9~99.6 ft·lb	2.75~13.76 kgf·m	L75 x W45 x H40	198	12 / 48
34407-1A-1	1/2"	40~200 N·m	29.5~147.5 ft·lb	4.08~20.38 kgf·m	L75 x W45 x H40	198.5	12 / 48