




3426E / 3436E / 3446E

3446E-HG



雙刻度雙向板型扳手

- 雙刻度 - 吋磅(或呎磅)與牛頓米(或公斤米)
- 容易調整扭力
- 品質符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 4\%$ (正轉)
- 順時計 / 逆時計使用
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上



Item	Size inch		Nm	Torque Range		kg.m		
				ft-lb	in-lb			
3426E-1HG	1/4"	352	2.5~11 N·m	2~8 ft·lb	20~100 in·lb	0.3~1.2 kgf·m	630	1 / 12
3436E-1HG	3/8"	352	2.5~11 N·m	2~8 ft·lb	20~100 in·lb	0.3~1.2 kgf·m	740	1 / 12
3436E-2HG	3/8"	450	7~33 N·m	5~24 ft·lb	60~300 in·lb	0.7~3.4 kgf·m	870	1 / 12

Item	Size inch		Nm	Torque		Range	kg.m		
				ft-lb		in-lb			
3436E-3HG	3/8"	505	14~68 N·m	10~50 ft·lb		125~600 in·lb	1.4~7 kgf·m	1210	1 / 12
3446E-1HG	1/2"	555	25~135 N·m	20~100 ft·lb		200~1200 in·lb	3~14 kgf·m	1640	1 / 12
3446E-2HG	1/2"	590	50~225 N·m	40~160 ft·lb		400~2000 in·lb	5~23 kgf·m	1710	1 / 12
3446E-3HG	1/2"	803	70~330 N·m	50~250 ft·lb		600~3000 in·lb	7~35 kgf·m	3440	1 / 6