



34466-FG



扁管視窗型扭力扳手

- 雙刻度 - 牛頓米與呎磅
- 握把中間有大字的牛頓米數值，能容易調整到自己所需扭力值
- 可快速調整固定扭力旋鈕
- 耐用機構設計，使用精準度可超過10,000次
- 品質符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 3\%$ (正轉)
- 3/4" DR. 扭力扳手為圓管



Item	Gear Square Teeth Drive	Torque Range Nm / ft.lb.	Incr. Overall Length (mm)	  
34266-1FG	24 1/4"	5-25 N·m (3.6-18 ft·lb)	0.1 N·m 296	410 1 / 12
34366-1FG	32 3/8"	10-50 N·m (7.4-37 ft·lb)	0.25 N·m 333	470 1 / 12
34466-1FG	32T 1/2"	20-100 N·m (15-75 ft·lb)	0.5 N·m 400	820 1 / 12

Item	Gear Square Teeth Drive	Torque Range Nm / ft.lb.	Incr. Overall Length (mm)	  
34466-2FG	32T 1/2"	40-200 N·m (30-150 ft·lb)	1 N·m 500	1300 1 / 12
34466-3FG	32T 1/2"	60-300 N·m (45-220 ft·lb)	1 N·m 633	1470 1 / 12
34666-1FG	24 3/4"	100-600 N·m (75-440ft·lb)	2 N·m 1040	4650 1 / 2
34666-2FG	24 3/4"	150-800 N·m (110-590 ft·lb)	2 N·m 1235	5450 1 / 2
34666-3FG	24 3/4"	200-1000 N·m (150-740 ft·lb)	2 N·m 1238	5450 1 / 2