



34462-CG



雙刻度雙向快脫式扭力扳手(英吋磅 / 英呎磅 & 牛頓米)

- 雙刻度 - 吋磅(或呎磅)與牛頓米
- 品質符合 DIN ISO 6789:2017 & ASME B107.300-2010
- 扭力公差 $\pm 3\%$ (正轉)
- 順時計 / 逆時計使用
- 扭力產品必須定期回公正單位做扭力校正以確保扭力值準確。建議的校正時間為使用一年或者是使用5,000次以上



Item	Square Drive	Torque Range Nm	Incr.	Torque Range ft · lb	Incr.	Gear Teeth	Overall Length mm		
34262-1CG	1/4"	40~200 in·lb	1 in·lb	5.1~22.0 N·m	0.12 N·m	24	324	640	1/12
34362-1CG	3/8"	40~200 in·lb	1 in·lb	5.1~22.0 N·m	0.12 N·m	24	324	640	1/12
34362-2CG	3/8"	15~80 ft·lb	0.5 ft·lb	23.7~105 N·m	0.7 N·m	32	435	1300	1/12

Item	Square Drive	Torque Range Nm	Incr.	Torque Range ft · lb	Incr.	Gear Teeth	Overall Length mm		
34462-1CG	1/2"	20~150 ft·lb	1 ft·lb	34~197 N·m	1.4 N·m	32	521	1590	1/12
34462-2CG	1/2"	50~250 ft·lb	1 ft·lb	75~332 N·m	1.4 N·m	32	613	1810	1/12
34662-1CG	3/4"	100~450 ft·lb	5 ft·lb	169~576 N·m	6.8 N·m	24	1048	5500	1/2
34662-2CG	3/4"	100~600 ft·lb	5 ft·lb	169~779 N·m	6.8 N·m	24	1234	5600	1/2
34662-3CG	3/4"	150~750 ft·lb	5 ft·lb	237~983 N·m	6.8 N·m	24	1238	6150	1/2
34862-1CG	1"	150~750 ft·lb	5 ft·lb	237~983 N·m	6.8 N·m	24	1238	6150	1/2
34862-2CG	1"	200~1000 ft·lb	5 ft·lb	305~1322 N·m	6.8 N·m	24	1850	10510	1/2