



Flexible Ring Socket Wrench & Set

- Chrome vanadium alloy steel
- Polished, chrome plated
- 4 ball retaining grooves

3350M

3/8"

- Flexible head folds up to 200°
- Combine use with F-handle, handle, T-handle speed-handle
- Suitable for all hydraulic, fuel, oil brake, A/C, auto tool and air line work
- DIN 3120



KT NO.	mm	D1 mm	D2 mm	L mm	g	kg
335008M	8	15.0	18.8	45.0	44	12 / 360
335009M	9	18.0	18.8	49.0	49	12 / 360
335010M	10	18.0	18.8	49.0	48	12 / 360
335011M	11	22.0	18.8	53.0	58	12 / 360
335012M	12	22.0	18.8	53.0	58	12 / 360
335013M	13	26.0	18.8	60.0	83	12 / 240
335014M	14	26.0	18.8	60.0	80	12 / 240
335015M	15	27.0	18.8	60.0	77	12 / 240
335016M	16	32.0	24.7	73.5	160	6 / 96
335017M	17	33.0	24.7	73.5	159	6 / 96
335018M	18	33.0	24.7	73.5	155	6 / 96
335019M	19	32.0	24.7	73.5	154	6 / 96



Flexible Crowfoot Socket Wrench & Set

- Chrome vanadium alloy steel
- Polished, chrome plated
- 4 ball retaining grooves

3351M

3/8"

- Flexible head folds up to 200°
- Combine use with F-handle, handle, T-handle speed-handle
- Suitable for all hydraulic, fuel, oil brake, A/C, auto tool and air line work
- DIN 3120



KT NO.	mm	D1 mm	D2 mm	L mm	g	kg
335108M	8	15.0	18.8	45.0	44	12 / 360
335109M	9	18.0	18.8	49.0	47	12 / 360
335110M	10	18.0	18.8	49.0	47	12 / 360
335111M	11	22.0	18.8	53.0	56	12 / 360
335112M	12	22.0	18.8	53.0	55	12 / 360
335113M	13	26.0	18.8	60.0	77	12 / 240
335114M	14	26.0	18.8	60.0	75	12 / 240
335115M	15	27.0	18.8	60.0	75	12 / 240
335116M	16	32.0	24.7	73.5	152	6 / 96
335117M	17	33.0	24.7	73.5	149	6 / 96
335118M	18	33.0	24.7	73.5	155	6 / 96
335119M	19	33.3	24.7	73.5	152	6 / 96

3602MR

3/8"

Metal case size (mm):
296 x 130 x 41 (0.89 cuft)



12
PC.

Contents



1.89



1 / 10



3350M

8, 9, 10, 11, 12, 13, 14, 15, 16,
17, 18, 19

3612MR

3/8"

Metal case size (mm):
296 x 130 x 41 (0.89 cuft)



12
PC.

Contents



1.89



1 / 10



3351M

8, 9, 10, 11, 12, 13, 14, 15, 16,
17, 18, 19