

Standard Impact Socket

- Material - chrome molybdenum alloy steel
- Finishing - phosphate sunk

4535M

1/2"

- DIN 3129, ISO 2725-2



KT NO.	mm	D1 mm	D2 mm	l mm	L mm		
453508M	8	15.0	25	7	38	67	10 / 200
453509M	9	16.3	25	7	38	67	10 / 200
453510M	10	17.6	25	8	38	70	10 / 200
453511M	11	18.8	25	8	38	71	10 / 200
453512M	12	20.0	25	9	38	72	10 / 200
453513M	13	21.2	25	10	38	72	10 / 200
453514M	14	22.5	25	10	38	77	10 / 200
453515M	15	23.8	30	11	38	112	10 / 160
453516M	16	25.0	30	11	38	112	10 / 160
453517M	17	26.2	30	12	38	115	10 / 160
453518M	18	27.5	30	13	38	115	10 / 160
453519M	19	28.8	30	13	38	120	10 / 160
453520M	20	29.5	30	13	38	120	10 / 160
453521M	21	30.0	30	14	40	125	8 / 160
453522M	22	32.4	30	14	40	143	8 / 160
453523M	23	33.2	30	15	40	143	8 / 160
453524M	24	34.4	30	15	42	152	6 / 120
453525M	25	36.0	30	15	42	168	6 / 120
453526M	26	37.0	30	15	42	173	6 / 120
453527M	27	38.0	30	16	44	176	6 / 120
453528M	28	41.0	30	16	44	194	6 / 120
453529M	29	41.0	30	17	44	194	6 / 120
453530M	30	42.0	30.5	17	44	201	6 / 120
453532M	32	46.0	30	19	44	205	6 / 120
453533M	33	46.0	30	19	46	227	6 / 96
453534M	34	46.0	30	20	46	231	6 / 96
453536M	36	47.0	30	20	46	248	6 / 96
453538M	38	50.0	30	21	50	241	6 / 60
453539M	39	51.0	30	22	50	240	6 / 60
453541M	41	52.0	30	22	52	283	6 / 60
453546M	46	59.0	30	23	55	408	4 / 32

4535S

1/2"

- ANSI/ASME B107.2



KT NO.	inch	D1 mm	D2 mm	l mm	L mm		
453510S	5/16	14	25	7	38	67	10 / 200
453512S	3/8	17	25	7	38	70	10 / 200
453514S	7/16	18	25	8	38	71	10 / 200
453516S	1/2	20	25	10	38	72	10 / 200
453518S	9/16	22	25	10	38	77	10 / 200
453520S	5/8	24	25	11	38	112	10 / 160
453522S	11/16	26	30	12	38	115	10 / 160
453524S	3/4	28	30	13	38	120	10 / 160
453526S	13/16	30	30	14	40	125	8 / 160
453528S	7/8	32	30	14	40	143	8 / 160
453530S	15/16	34	30	15	42	152	6 / 120
453532S	1	36	30	15	42	168	6 / 120
453534S	1-1/16	38	30	16	44	176	6 / 120
453536S	1-1/8	41	30	17	44	194	6 / 120
453538S	1-3/16	42	30.5	17	44	201	6 / 120
453540S	1-1/4	46	30	18	44	205	6 / 120

