

# Spark Plug Socket



KT No. & D1

## 3630

## 3660

## 3635

## 3665 3/8"

- 6 / 12 points
- Size combined- 16.0mm (5/8") - 20.8mm (13/16")
- Inside sleeve - rubber / magnet
- DIN 3120



KT NO.	Type	Size inch	Size mm	D mm	L mm		
363016	12 points Rubber	5/8	16.0	21	70	100	10 / 200
366016	12 points Magnet	5/8	16.0	21	70	105	10 / 200
363021	12 points Rubber	13/16	20.8	27.7	70	150	12 / 120
366021	12 points Magnet	13/16	20.8	27.7	70	155	12 / 120
363516	6 points Rubber	5/8	16.0	21	70	100	10 / 200
366516	6 points Magnet	5/8	16.0	21	70	105	10 / 200
363521	6 points Rubber	13/16	20.8	27.7	70	145	12 / 120
366521	6 points Magnet	13/16	20.8	27.7	70	150	12 / 120



## 36A0

## 36A5

## 3/8"

- 6 / 12 points
- Size combined - 14.0mm, 18.0mm
- Inside sleeve - spring
- DIN 3120



Spring

KT NO.	Type	Size mm	D mm	L mm		
36A014	12 points	14.0	18.5	63	65.4	12 / 192
36A018	12 points	18.0	23.8	63	98.0	8 / 128
36A514	6 points	14.0	18.5	63	69.4	12 / 192
36A518	6 points	18.0	23.8	63	98.2	8 / 128



## 36B5

## 3/8"


## 36B0

## 36C0

## 36D0

## 3/8"

- Inside sleeve - rubber
- DIN 3120
- 36C014 & 36D014 are suitable for BMW, Mini, RENAULT Clio / Twingo / Kangoo type, PEUGEOT 206 1.4 16V, CITROEN C5 HPI



rubber

KT NO.	Type	Size mm	D mm	L mm		
36B514	6 points	14.0	18.5	63	80.3	12 / 192
36B014	12 points	14.0	18.5	63	80.3	12 / 192
36B018	12 points	18.0	24.7	65	106.5	8 / 128
36C014	12 points	14.0	18.5	90	112.8	12 / 144
36D014	12 points	14.0	18.5	250	291.4	6 / 54



Rubber

