

Stubby Combination Wrench & Set


• Pouch material : Nylon

KT No. & D1



10D0

- Short pattern design enables greater access in confined spaces
- Chrome vanadium alloy steel
- Chrome plated
- DIN3113



KT NO.	Size mm	D1	D2	H1	H2	L mm		
10D0-08	8	18.1	13.8	4.6	6.0	85	20	20 / 360
10D0-09	9	19.3	14.5	4.8	6.4	90	25	20 / 360
10D0-10	10	20.5	15.1	4.8	6.4	95	27	20 / 360
10D0-11	11	22.7	16.7	5.9	7.9	100	45	20 / 360
10D0-12	12	24.7	18.0	6.2	8.3	105	49	20 / 360
10D0-13	13	27.2	19.1	6.5	8.7	110	59	20 / 360
10D0-14	14	28.8	21.4	7.0	9.2	115	65	15 / 270
10D0-15	15	31.0	22.4	7.4	9.7	120	73	15 / 270
10D0-16	16	33.0	23.8	7.8	10.3	125	85	15 / 270
10D0-17	17	35.0	26.2	8.1	10.7	130	116	15 / 180
10D0-18	18	37.0	27.3	8.6	11.3	135	123	15 / 180
10D0-19	19	39.0	28.6	9.0	11.8	140	135	12 / 144

1282MR

KT NO. Contents

1.03

1 / 24



8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19



12 PC.


Single Open End Wrench



Please wear proper safety gear while working.

10F0

- Features: The open end is thicker for very high tightening torques. examples: public work, rail worksite, naval construction, agriculture, oil platforms, metallic construction
- Hanging hole at end of handle: wrenches stored on panel or hung to avoid loss or fall
- Chrome vanadium alloy steel
- Finished with phosphate sunk
- DIN 894



KT NO.	Size mm	L mm		
10F0-17P	17	178	107	10 / 120
10F0-19P	19	178	107	10 / 120
10F0-21P	21	203	161	10 / 100
10F0-22P	22	203	161	10 / 100
10F0-23P	23	220	203	8 / 80
10F0-24P	24	220	203	8 / 80
10F0-26P	26	240	290	6 / 60
10F0-27P	27	240	290	6 / 60
10F0-29P	29	267	341	6 / 48
10F0-30P	30	267	335	6 / 48
10F0-32P	32	285	410	5 / 30

KT NO.	Size mm	L mm		
10F0-36P	36	317	556	5 / 30
10F0-38P	38	320	740	5 / 30
10F0-41P	41	340	875	4 / 24
10F0-46P	46	395	1060	3 / 12
10F0-50P	50	425	1402	1 / 12
10F0-55P	55	425	1403	1 / 12
10F0-60P	60	470	2544	1 / 6
10F0-65P	65	470	2441	1 / 6
10F0-70P	70	500	3457	1 / 6
10F0-75P	75	500	3333	1 / 6