

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted

10mm Hex size shank driver




order unit : one blister card

1600U



- For torx head screw
- Tamper resistant type
- 36 / 80mmL




KT NO.	Size	Overall length (mm)			
163610U	T10H	36	16.9	12 / 120	
163615U	T15H	36	17.3	12 / 120	
163620U	T20H	36	17.6	12 / 120	
163625U	T25H	36	17.8	12 / 120	
163627U	T27H	36	18.2	12 / 120	
163630U	T30H	36	18.3	12 / 120	
163640U	T40H	36	19.9	12 / 120	
163645U	T45H	36	20.9	12 / 120	
163650U	T50H	36	22.9	12 / 120	
163655U	T55H	36	28.0	12 / 120	
163660U	T60H	36	32.6	12 / 120	
168010U	T10H	80	46.3	6 / 60	
168015U	T15H	80	46.5	6 / 60	
168020U	T20H	80	46.8	6 / 60	
168025U	T25H	80	47.1	6 / 60	
168027U	T27H	80	47.2	6 / 60	
168030U	T30H	80	47.2	6 / 60	
168040U	T40H	80	48.0	6 / 60	
168045U	T45H	80	49.1	6 / 60	
168050U	T50H	80	50.0	6 / 60	
168055U	T55H	80	52.3	6 / 60	
168060U	T60H	80	70.4	6 / 60	

1600M

Spline head



- 36 / 80mmL



KT NO.	Size	Overall length (mm)			
163605M	M5	36	18.3	12 / 120	
163606M	M6	36	18.7	12 / 120	
163608M	M8	36	19.8	12 / 120	
163610M	M10	36	22.4	12 / 120	
163612M	M12	36	27.7	12 / 120	
168005M	M5	80	47.2	6 / 60	
168006M	M6	80	47.9	6 / 60	
168008M	M8	80	49.0	6 / 60	
168010M	M10	80	51.6	6 / 60	
168012M	M12	80	70.1	6 / 60	

Bit Display Box

87352

- Overall size -W 318 x D 235 x H 183 mm
- Weight - 1.3 Kg / Cuff - 0.4

