

Nut Splitter Set

9TD062

- For removing stubborn nuts or over tightened bolts without damaging the bolt thread
- Suitable for nuts to a tensile class 6
- Do not overtighten to prevent damage to the threads under the nut

⚖️ 609.4 📦 12 / 36

KT NO.	Capacity		Hex (mm)
	inch	mm	
9TD062	1/2"~5/8"	12~16	14
9TD063	5/8"~7/8"	16~22	19



9TD064

⚖️ 1895 📦 1 / 12

KT NO.	Capacity		Hex (mm)
	inch	mm	
9TD601	5/16"~1/2"	9~12	12
9TD602	1/2"~5/8"	12~16	14
9TD603	5/8"~7/8"	16~22	19
9TD604	7/8"~1-1/8"	22~27	21




1/2" DR. Damaged Nuts Remover Socket & Set

9TD403


1/2"

- Made of top quality SNCM alloy steel, provide good wear resistance and durability
- Ideal for the removal of rounded, damaged or corroded nuts, bolts, oil drain plugs, marine nuts and bolts, exhaust manifold nuts, pipe nozzle, and studs
- No pounding, chisels or torches are needed

KT NO.	D1 mm	D2 mm	ℓ mm	L mm	⚖️	📦
9TD403-12M	18	22	11	50	77.0	10 / 180
9TD403-13M	20	22	11	50	84.0	10 / 180
9TD403-14M	21	22	11	50	85.0	10 / 180
9TD403-17M	24.5	25	15	50	117.0	10 / 180
9TD403-19M	27	27	15	50	135.0	8 / 80
9TD403-21M	29.4	27	16	50	138.4	8 / 80
9TD403-22M	30.5	27	17	50	140.6	8 / 80



CAUTION



Can't be used with pneumatic wrench



9TD035MR

1/2"

Contents ⚖️ 0.52 📦 4 / 36

9TD403 12, 13, 14, 17, 19

8740705

