

Heavy Duty Adjustable Torque Wrench

Design for easy torque adjustment

Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010

Tolerance of torque $\pm 3\%$ (CW)

CW/CCW Direction



34862-2CF, 34862-2DF
34862-2EF, 34862-2FF



In order to ensure correct torque the extension bar must be used



34862-2CG, 34862-2DG
34862-2EG, 34862-2FG
34862-2GG

Dual Scale - English & Newton Meter (lbf-ft & N-m)

KT NO.	Square drive	Torque Range lbf-ft	Incr.	Torque range N-m	Incr.	Overall length mm	kg	Box/Kit
34862-2CG	1"	200~1000 lbf-ft	5 lbf-ft	305~1322 N-m	6.8 N-m	1850	12.20	1 / 2
34862-2CF	1"	200~1000 lbf-ft	5 lbf-ft	305~1322 N-m	6.8 N-m	1850	12.20	1 / 2

Single scale - Newton Meter (N-m)

KT NO.	Square drive	Torque range N-m	Incr.	Overall length mm	kg	Box/Kit
34862-1DF	1"	200~1000 N-m	5 N-m	1238	6.11	1 / 2
34862-2DF	1"	300~1500 N-m	10 N-m	1850	12.20	1 / 2
34862-2DG	1"	300~1500 N-m	10 N-m	1850	12.20	1 / 2

Single scale - English (lbf-ft)

KT NO.	Square drive	Torque Range lbf-ft	Incr.	Overall length mm	kg	Box/Kit
34862-2EG	1"	200~1000 lbf-ft	5 lbf-ft	1850	12.20	1 / 2
34862-2EF	1"	200~1000 lbf-ft	5 lbf-ft	1850	12.20	1 / 2



Dual Scale - Newton Meter & English (N-m & lbf-ft)

KT NO.	Square drive	Torque range N-m	Incr.	Torque range lbf-ft	Incr.	Overall length mm	kg	Box/Kit
34862-2FF	1"	300~1500 N-m	10 N-m	258~1070 lbf-ft	7.4 lbf-ft	1850	12.20	1 / 2
34862-2FG	1"	300~1500 N-m	10 N-m	258~1070 lbf-ft	7.4 lbf-ft	1850	12.20	1 / 2

Dual Scale - Kilogram-force meter & Newton Meter (kgf-m & N-m)

KT NO.	Square drive	Torque range kgf-m	Incr.	Torque range N-m	Incr.	Overall length mm	kg	Box/Kit
34862-2GG	1"	30~150 Kgf-m	1 Kgf-m	343~1422 N-m	5 N-m	1850	12.20	1 / 2

