

Power Driving

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, phosphate sunk
- Magnetic **1/4"** Hex size shank driver



1004H

- For Hexagon head screws
- DIN ISO 2351-3
- Short neck (9.5mm) type



6
PC.

KT NO.	PC.	Overall length (mm)		Contents		
1004A6HQ	6	50	7150H	H2, H2.5, H3, H4, H5, H6	0.09	10 / 120
1004B6HQ	6	70	7170H	H2, H2.5, H3, H4, H5, H6	0.09	10 / 120
1004C6HQ	6	110	7111H	H2, H2.5, H3, H4, H5, H6	0.15	10 / 120
1004D6HQ	6	150	7115H	H2, H2.5, H3, H4, H5, H6	0.20	6 / 72

1004T

- For TORX head screws
- Short neck (9.5mm) type



6
PC.

KT NO.	PC.	Overall length (mm)		Contents		
1004A6TQ	6	50	7150T	T15, T20, T25, T27, T30, T40	0.09	10 / 120
1004B6TQ	6	70	7170T	T15, T20, T25, T27, T30, T40	0.09	10 / 120
1004C6TQ	6	110	7111T	T15, T20, T25, T27, T30, T40	0.15	10 / 120
1004D6TQ	6	150	7115T	T15, T20, T25, T27, T30, T40	0.20	6 / 72

1004U

- For Tamper Resistant TORX head screws
- Short neck (9.5mm) type



6
PC.

KT NO.	PC.	Overall length (mm)		Contents		
1004A6UQ	6	50	7150U	T10H, T15H, T20H, T25H, T27H, T30H	0.09	10 / 120
1004B6UQ	6	70	7170U	T10H, T15H, T20H, T25H, T27H, T30H	0.09	10 / 120
1004C6UQ	6	110	7111U	T10H, T15H, T20H, T25H, T27H, T30H	0.15	10 / 120
1004D6UQ	6	150	7115U	T10H, T15H, T20H, T25H, T27H, T30H	0.20	6 / 72