

Spark Plug Socket

KT No. & D1

**3630****3660****3635****3665****3670****3675**

- 6 / 12 points
- Size combined- 16.0mm (5/8") - 20.8mm (13/16")
- Inside sleeve - rubber / magnet
- DIN 3120



KT NO.	Type	Size		D mm	L mm		
		inch	mm				
363016	12 points Rubber	5/8	16.0	21	70	85	10 / 200
363021	12 points Rubber	13/16	20.8	27.7	70	149	12 / 120
363516	6 points Rubber	5/8	16.0	21	70	88	10 / 200
363521	6 points Rubber	13/16	20.8	27.7	70	153	12 / 120
366516	6 points Magnet	5/8	16.0	21	70	89	10 / 200
366521	6 points Magnet	13/16	20.8	27.7	70	155	12 / 120

367018 料號已失效 2025/7/11

367021	12 points Metal clip	13/16 20.8	27.7	70	167	12 / 120
---------------	-------------------------	------------	------	----	-----	----------

367516 料號已失效 2025/7/11

367518	6 points Metal clip	- 18.0	23.8	63	91	12 / 120
---------------	------------------------	--------	------	----	----	----------

367521 料號已失效 2025/7/11



363016



363021



366021



363516




366516




363521



366521



Rubber




Magnet



367516



367018



Metal clip


Glow Plug Socket & Set

3785M

- The socket has a Sprung-loaded clip with ball bearing end to stop the glow plug from falling out
- Suitable for the removal of glow plugs in most diesel engines

**3716MR**

- Blow case size (mm):
- 260 x 160 x 64 (0.094 cuft)

6
PC.

KT NO.	 mm	D1 mm	D2 mm	L mm		 / 
378508M	8	13.5	17.8	118	131	10 / 100
378509M	9	13.5	17.8	118	120	10 / 100
378510M	10	13.5	17.8	118	123	10 / 100
378512M	12	17.8	17.8	118	147	10 / 100
378514M	14	17.8	17.8	118	139	10 / 100
378516M	16	19.8	17.8	118	154	10 / 100

Contents



1.23



1 / 10



3785M

8, 9, 10, 12, 14, 16