


Accessory

KT No. & D1

4791R

1/2"

- Univesal joint
- DIN 3120, ISO 3316




KT NO.	Overall length inch mm		
4791R	3 77.5	159	5 / 100

4794



1/2"


- Univesal joint
- 30° rotation
- Short pattern design enables greater access in confined spaces



KT NO.	Overall length inch mm		
4794	2-3/8 60	105	5 / 180

4793

1/2"



KT NO.	Overall length inch mm		
4793	2-5/16 59	18	20 / 600

9113PR

1/4" 3/8" 1/2"

- Universal joint
- Ball point type universal joint & with hex locking design
- Short pattern design enables greater access in confined spaces



3 PC.

Contents		
2793	0.20	6 / 108
3793		
4793		

4844R

1/2"

- 1/2 " drive (1/2 " F x 1/2 " M)
- Finish : Chrome Alloy Steel, chrome plated
- Reversible
- 5° gear action degree (72 teeth)
- Apply to 1/2" accessory (Ex : 4453-15F)
- Apply to 1/2 " torque wrench (Ex : 3446E series)

KT NO.	Overall length inch mm		
4844R	2-7/16 62	250	1 / 64



PAT.


Outer diameter 37 x Height 62 mm

KT NO.	Contents		
4122FR	4844R 4453-15F	880	1 / 20
4122FR01	4844R 4453-18F	958	1 / 20

Magnetic Insert

91000M

- Magnetic insert for sockets
- Powerful retention force
- Reusable
- 11 PC. set, for metric sockets



KT NO.	Size (mm)		
91000M	8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm	42	12 / 144



11 PC.