

Thin Wall Impact Socket


KT No. & D1



6835M

3/4"

- DIN 3121




KT NO.	mm	D1 mm	D2 mm	l mm	L mm	g	g	g
683517M	17	28.0	44	16	60	346	6 / 48	
683519M	19	30.0	44	16	60	351	6 / 48	
683521M	21	33.0	44	18	60	369	6 / 48	
683522M	22	34.0	44	18	60	372	6 / 48	
683523M	23	35.0	44	23	60	373	6 / 48	
683524M	24	36.5	44	23	60	382	6 / 48	
683526M	26	39.0	44	25	80	397	1 / 24	
683527M	27	40.0	44	26	80	424	1 / 24	
683529M	29	43.0	44	26	80	455	1 / 24	
683530M	30	44.0	44	26	80	555	1 / 24	
683532M	32	46.5	44	26	80	512	1 / 24	

6935M

3/4"

- DIN 3121




KT NO.	mm	D1 mm	D2 mm	l mm	L mm	g	g	g
693519M	19	30.0	44	16	90	513	1 / 24	
693521M	21	33.0	44	18	90	546	1 / 24	
693522M	22	34.0	44	18	90	541	1 / 24	
693523M	23	35.0	44	23	90	519	1 / 24	
693524M	24	36.5	44	23	90	573	1 / 24	
693526M	26	39.0	44	25	90	578	1 / 24	
693527M	27	40.0	44	27	90	574	1 / 24	
693529M	29	43.0	44	27	90	578	1 / 24	
693530M	30	44.0	44	27	90	622	1 / 24	
693532M	32	46.5	44	30	90	683	1 / 24	

6935S

3/4"

- ANSI / ASME B107.2




KT NO.	inch	D1 mm	D2 mm	l mm	L mm	g	g	g
693524S	3/4	30.0	38	16	90	370	1 / 24	
693526S	13/16	33.0	38	18	90	380	1 / 24	
693528S	7/8	34.0	38	18	90	385	1 / 24	
693530S	15/16	36.5	38	23	90	415	1 / 24	
693532S	1	38.0	38	23	90	500	1 / 24	
693534S	1-1/16	40.0	44	25	90	654	1 / 24	
693536S	1-1/8	43.0	44	25	90	680	1 / 24	
693538S	1-3/16	44.0	44	27	90	684	1 / 24	
693540S	1-1/4	46.5	44	30	90	733	1 / 24	

Impact Star Socket

6575M

3/4"

- For torx external screw
- DIN 3121




KT NO.	Size	D1 mm	D2 mm	l mm	L mm	g	g	g
657524M	E24	32.5	44.0	17.0	50	334	6 / 48	
657526M	E26	35.0	44.0	19.0	60	402	6 / 48	
657528M	E28	36.5	44.0	25.5	60	401	6 / 48	
657530M	E30	37.5	44.0	27.0	65	428	1 / 24	
657532M	E32	39.5	44.0	29.0	65	447	1 / 24	

Deep Impact Star Socket

6475M

3/4"

- For torx external screw
- DIN 3121
- For the operation of cylinder head bolts
- E18 application MAN M 2000 / Bus with D 08 engine
- E20 application MAN F 2000 / F 90 / F 8 / Bus with D 25 and D 28 engines
- E24 application MAN D20 engine



KT NO.	Size	D1 mm	D2 mm	l mm	L mm	g	g	g
647518M	E18	26.5	44.0	12.5	110	592	1 / 10	
647520M	E20	29.0	44.0	14.0	110	627	1 / 10	
647522M	E22	31.0	44.0	15.0	110	662	1 / 10	
647524M	E24	32.5	44.0	17.0	110	693	1 / 10	

Rear Wheel Socket


KT No. & D1



6514M

3/4"

- 4 points
- DIN 3121



KT NO.	Size	D1 mm	D2 mm	l mm	L mm	g	g	g
651417M	17	39.8	34	28	53	353	1 / 24	
651419M	19	39.8	34	28	53	339	1 / 24	
651420M	20	41.8	36	28	53	381	1 / 24	
651421M	21	41.8	36	28	53	369	1 / 24	