




## Deep Impact Socket

### 8435M



- DIN 3121




| KT NO.  | mm | D1 mm | D2 mm | ℓ mm | L mm | g    | kg     |
|---------|----|-------|-------|------|------|------|--------|
| 843524M | 24 | 41    | 54    | 25   | 90   | 874  | 1 / 24 |
| 843527M | 27 | 44    | 54    | 25   | 90   | 871  | 1 / 24 |
| 843528M | 28 | 45    | 54    | 25   | 90   | 887  | 1 / 24 |
| 843530M | 30 | 48    | 54    | 28   | 90   | 908  | 1 / 24 |
| 843532M | 32 | 51    | 54    | 28   | 90   | 953  | 1 / 24 |
| 843533M | 33 | 52    | 54    | 28   | 92   | 1016 | 1 / 24 |
| 843534M | 34 | 53    | 54    | 28   | 92   | 988  | 1 / 24 |
| 843535M | 35 | 54    | 54    | 28   | 92   | 1020 | 1 / 24 |
| 843536M | 36 | 56    | 54    | 32   | 92   | 1034 | 1 / 24 |
| 843538M | 38 | 58    | 54    | 32   | 92   | 1048 | 1 / 24 |
| 843540M | 40 | 60    | 54    | 32   | 92   | 1094 | 1 / 24 |
| 843541M | 41 | 61    | 54    | 32   | 92   | 1103 | 1 / 24 |
| 843542M | 42 | 64    | 54    | 32   | 92   | 1236 | 1 / 24 |
| 843546M | 46 | 68    | 54    | 35   | 95   | 1329 | 1 / 10 |
| 843548M | 48 | 70    | 54    | 35   | 95   | 1378 | 1 / 10 |
| 843550M | 50 | 73    | 54    | 35   | 95   | 1484 | 1 / 10 |
| 843552M | 52 | 75    | 54    | 40   | 100  | 1594 | 1 / 6  |
| 843554M | 54 | 78    | 54    | 40   | 100  | 1714 | 1 / 6  |
| 843555M | 55 | 79    | 54    | 40   | 100  | 1706 | 1 / 6  |
| 843558M | 58 | 83    | 54    | 42   | 100  | 1887 | 1 / 6  |
| 843560M | 60 | 86    | 54    | 42   | 100  | 2022 | 1 / 6  |
| 843565M | 65 | 92    | 54    | 50   | 110  | 2133 | 1 / 6  |
| 843570M | 70 | 97    | 54    | 59   | 110  | 2285 | 1 / 6  |

### 8435S



- ANSI / ASME B107.1




| KT NO.  | inch    | D1 mm | D2 mm | ℓ mm | L mm | g    | kg     |
|---------|---------|-------|-------|------|------|------|--------|
| 843530S | 15/16   | 40.8  | 54    | 25   | 90   | 872  | 1 / 24 |
| 843532S | 1       | 42    | 54    | 25   | 90   | 847  | 1 / 24 |
| 843534S | 1-1/16  | 44    | 54    | 25   | 90   | 868  | 1 / 24 |
| 843536S | 1-1/8   | 46.3  | 54    | 25   | 90   | 911  | 1 / 24 |
| 843538S | 1-3/16  | 48    | 54    | 28   | 90   | 926  | 1 / 24 |
| 843540S | 1-1/4   | 51    | 54    | 28   | 90   | 980  | 1 / 24 |
| 843542S | 1-5/16  | 52    | 54    | 28   | 92   | 1010 | 1 / 24 |
| 843544S | 1-3/8   | 54    | 54    | 28   | 92   | 1022 | 1 / 24 |
| 843546S | 1-7/16  | 56    | 54    | 32   | 92   | 1017 | 1 / 24 |
| 843548S | 1-1/2   | 58    | 54    | 32   | 92   | 1048 | 1 / 24 |
| 843550S | 1-9/16  | 60    | 54    | 32   | 92   | 1096 | 1 / 24 |
| 843552S | 1-5/8   | 61    | 54    | 32   | 92   | 1097 | 1 / 24 |
| 843554S | 1-11/16 | 64    | 54    | 32   | 92   | 1211 | 1 / 24 |
| 843556S | 1-3/4   | 67    | 54    | 32   | 92   | 1312 | 1 / 12 |
| 843558S | 1-13/16 | 68    | 54    | 35   | 95   | 1322 | 1 / 12 |
| 843560S | 1-7/8   | 70    | 54    | 35   | 95   | 1382 | 1 / 6  |
| 843562S | 1-15/16 | 72    | 54    | 35   | 95   | 1450 | 1 / 6  |
| 843564S | 2       | 74    | 54    | 35   | 95   | 1510 | 1 / 6  |
| 843566S | 2-1/16  | 75    | 54    | 40   | 100  | 1589 | 1 / 6  |
| 843568S | 2-1/8   | 78    | 54    | 40   | 100  | 1729 | 1 / 6  |
| 843570S | 2-3/16  | 79    | 54    | 40   | 100  | 1646 | 1 / 6  |
| 843572S | 2-1/4   | 82    | 54    | 42   | 100  | 1837 | 1 / 6  |

## Thin Wall Impact Socket

### 8835M



- Thin wall version
- 6 points
- Metric size
- DIN 3121



| KT NO.  | mm | D1 mm | D2 mm | ℓ mm | L mm | g   | kg     |
|---------|----|-------|-------|------|------|-----|--------|
| 883524M | 24 | 38.0  | 54    | 26   | 80   | 690 | 1 / 24 |
| 883527M | 27 | 42.0  | 54    | 26   | 80   | 710 | 1 / 24 |
| 883529M | 29 | 44.0  | 54    | 26   | 80   | 750 | 1 / 24 |
| 883530M | 30 | 46.0  | 54    | 30   | 80   | 750 | 1 / 24 |
| 883532M | 32 | 48.0  | 54    | 30   | 80   | 743 | 1 / 24 |
| 883533M | 33 | 49.0  | 54    | 30   | 80   | 776 | 1 / 24 |
| 883534M | 34 | 50.0  | 54    | 30   | 80   | 761 | 1 / 24 |
| 883535M | 35 | 52.0  | 54    | 32   | 80   | 800 | 1 / 24 |
| 883536M | 36 | 53.0  | 54    | 32   | 80   | 781 | 1 / 24 |
| 883538M | 38 | 56.0  | 54    | 32   | 80   | 831 | 1 / 24 |
| 883541M | 41 | 59.5  | 54    | 32   | 80   | 882 | 1 / 24 |

## Rear Wheel Socket

### 8514M

### 8514S

### 8524M



- 4 points
- DIN 3121




8514M



8524M



8514S



| KT NO.  | SQ    | D1 mm | D2 mm | ℓ mm | L mm | g   | kg     |
|---------|-------|-------|-------|------|------|-----|--------|
| 851417M | 17    | 40.0  | 54    | 30.0 | 60   | 612 | 1 / 24 |
| 851419M | 19    | 42.0  | 54    | 30.0 | 60   | 611 | 1 / 24 |
| 851420M | 20    | 43.0  | 54    | 30.0 | 60   | 625 | 1 / 24 |
| 851421M | 21    | 44.0  | 54    | 30.0 | 60   | 618 | 1 / 24 |
| 851422M | 22    | 45.5  | 54    | 30.0 | 60   | 629 | 1 / 24 |
| 852421M | 21    | 44.0  | 48    | 30.0 | 60   | 502 | 1 / 24 |
| 851426S | 13/16 | 44    | 54    | 30.0 | 60   | 617 | 1 / 24 |