

Impact Wrench

33811 / 33812

- Nickel chrome molybdenum square drive
- Variable speed trigger
- Muffled on handle exhaust



33851 / 33852

- Nickel chrome molybdenum square drive
- Variable speed trigger
- Muffled on handle exhaust



KT NO.	Square drive inch mm	Type Std/Long anvil	Std. bolt size inch mm	Free speed R.P.M.	Max. torque ft-lb N-m	Overall length inch mm	Air inlet inch	Air hose ID	Air pressure bar psi	Avg. air consumption L/min CFM	Sound DBA	Vib M/S2	Net weight kgs lbs
33811-150	1" 25.40	Std. anvil	1-1/4" M36	4000	1500 2033	14-19/32" 371	1/2" BSPT / NPT	3/4"	6.2 90	255 9.0	101.17	10.77	10.30 22.71 1 / 1
33812-150	1" 25.40	Long anvil	1-1/4" M36	4000	1500 2033	20-19/32" 523	1/2" BSPT / NPT	3/4"	6.2 90	255 9.0	100.40	6.13	11.30 24.91 1 / 1
33831-180	1" 25.40	Std. anvil	1-1/2" M38	4000	1800 2440	14-19/32" 371	1/2" BSPT / NPT	3/4"	6.2 90	255 9.0	102.11	8.84	11.50 25.35 1 / 1
33832-180	1" 25.40	Long anvil	1-1/2" M38	4000	1800 2440	20-19/32" 523	1/2" BSPT / NPT	3/4"	6.2 90	255 9.0	103.99	6.60	12.50 27.56 1 / 1
33851-250	1" 25.40	Std. anvil	1-25/32" M45	3000	2500 3388	17-11/64" 436	1/2" BSPT / NPT	3/4"	6.2 90	411 14.5	101.15	6.30	15.80 34.83 1 / 1
33852-250	1" 25.40	Long anvil	1-25/32" M45	3000	2500 3388	24-7/8" 632	1/2" BSPT / NPT	3/4"	6.2 90	411 14.5	101.91	6.49	18.70 41.23 1 / 1
33911-250	1-1/2" 38.10	Std. anvil	1-25/32" M45	3000	2500 3388	17-53/64" 453	1/2" BSPT / NPT	3/4"	6.2 90	411 14.5	104.13	6.32	15.80 34.83 1 / 1
33912-250	1-1/2" 38.10	Long anvil	1-25/32" M45	3000	2500 3388	23-53/64" 605	1/2" BSPT / NPT	3/4"	6.2 90	411 14.5	103.90	6.53	18.70 41.23 1 / 1
33921-300	1-1/2" 38.10	Std. anvil	2" M50	3000	3000 4065	17-3/4" 451	1/2" BSPT / NPT	3/4"	6.2 90	453 16.0	104.52	8.86	19.70 43.43 1 / 1
33922-300	1-1/2" 38.10	Long anvil	2" M50	3000	3000 4065	25-15/32" 647	1/2" BSPT / NPT	3/4"	6.2 90	453 16.0	104.52	7.12	22.80 50.27 1 / 1