

Heavy Duty Adjustable Torque Wrench

- Design for easy torque adjustment
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque $\pm 3\%$ (CW)
- CW/CCW Direction



DG Series N.m

1/4" 34262

KT NO	Square drive	Torque range N.m	Incr.	Gear teeth	Overall length mm			DK
34262-2DG	1/4"	2~10 N.m	0.1 N.m	24	281	560	1/12	34262-1DK
34262-1DG	1/4"	4~20 N.m	0.1 N.m	24	324	640	1/12	34262-1DK
34262-3DG	1/4"	5~30 N.m	0.5 N.m	24	325	640	1/12	34262-1DK

3/8" 34362

KT NO	Square drive	Torque range N.m	Incr.	Gear teeth	Overall length mm			DK
34362-1DG	3/8"	4~20 N.m	0.1 N.m	24	324	640	1/12	34362-1DK
34362-3DG	3/8"	10~60 N.m	0.5 N.m	32	325	700	1/12	34362-2DK 34362-2xx/3xx
34362-2DG	3/8"	20~100 N.m	0.5 N.m	32	435	1300	1/12	34362-2DK 34362-2xx/3xx

1/2" 34462

KT NO	Square drive	Torque range N.m	Incr.	Gear teeth	Overall length mm			DK
34462-3DG	1/2"	20~100 N.m	1 N.m	32	436	1300	1/12	34462-3DK: 34462-3DG/3GG
34462-1DG	1/2"	40~200 N.m	1 N.m	32	521	1590	1/12	34462-1DK
34462-2DG	1/2"	60~340 N.m	2 N.m	32	613	1810	1/12	34462-1DK
34462-4DG	1/2"	80~400 N.m	2 N.m	32	613	1970	1/12	34462-1DK

3/4" 34662

KT NO	Square drive	Torque range N.m	Incr.	Gear teeth	Overall length mm			DK
34662-1DG	3/4"	100~600 N.m	5 N.m	24	1048	5500	1/2	34662-1DK
34662-2DG	3/4"	150~800 N.m	5 N.m	24	1234	5600	1/2	34662-1DK
34662-3DG	3/4"	200~1000 N.m	5 N.m	24	1238	6150	1/2	34662-1DK 34662-3DK1: 34662-3xxx series

1" 34862

KT NO	Square drive	Torque range N.m	Incr.	Gear teeth	Overall length mm			DK
34862-1DG	1"	200~1000 N.m	5 N.m	24	1238	6150	1/2	34862-2DK:series
34862-2DG	1"	300~1500 N.m	10 N.m	24	1850	10510	1/2	34862-2DK:series