

Heavy Duty 72 Teeth Adjustable Torque Wrench



- Colorful quick release button design
- Fixed head version allows using in narrow spaces
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- Tolerance of torque $\pm 3\%$ (CW)
- CW/CCW Direction

10,000
Precision
in use

$\pm 3\%$
Tolerance



72 Teeth Series N.m

1/4" 3426A

KT NO	Square drive	Torque range N.m	incr.	Gear teeth	Overall length mm			DK
3426A-1DG	1/4"	2~10 N.m	0.1 N.m	72	285	560	1/24	3426A-1DK02
3426A-2DG	1/4"	4~20 N.m	0.1 N.m	72	325	640	1/24	(series No.before 19106A)

3/8" 3436A

KT NO	Square drive	Torque range N.m	incr.	Gear teeth	Overall length mm			DK
3436A-2DG	3/8"	20~100 N.m	0.5 N.m	72	430	1300	1/12	3436A-2DK 3436A-2DK02 (series No.before 19106A) 3436A-2DK03 (series No.before 2209)

1/2" 3446A

KT NO	Square drive	Torque range N.m	incr.	Gear teeth	Overall length mm			DK
3446A-1DG	1/2"	40~200 N.m	1 N.m	72	490	1400	1/12	3446A-1DK 3446A-1DK02 (series No.before 19106A)
3446A-2DG	1/2"	60~340 N.m	2 N.m	72	590	1750	1/12	3446A-1DK03 (series No.before 2209)