

Window Type Adjustable Torque Wrench

- Adjustable torque wrench with window dual scale
- Tolerance of torque $\pm 3\%$ clockwise
- Dual scale in N·m and ft·lb conversion table on window
- Grip handle and large number NM on center handle for setup required torque
- Simple lock and unlock knob for quick in adjustment
- Durable mechanism with over 10,000 cycles within accuracy
- Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
- The 3/4" torque wrenches have a cylinder body

10,000
Precision
in use

$\pm 3\%$
Tolerance



1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

1/4" 34266

KT NO.	Gear teeth	Square drive	Torque range N·m	Incr.	Torque range ft·lb	Overall length mm			DK
34266-1FG	24	1/4"	5-25 N·m	0.1 N·m	3.6-18 ft·lb	296	410	1 / 12	2761DK

3/8" 34366

KT NO.	Gear teeth	Square drive	Torque range N·m	Incr.	Torque range ft·lb	Overall length mm			DK
34366-1FG	32	3/8"	10-50 N·m	0.25 N·m	7.4-37 ft·lb	333	470	1 / 12	34362-1DK

1/2" 34466

KT NO.	Gear teeth	Square drive	Torque range N·m	Incr.	Torque range ft·lb	Overall length mm			DK
34466-1FG	32	1/2"	20-100 N·m	0.5 N·m	15-75 ft·lb	398	820	1 / 12	34462-3DK
34466-2FG	32	1/2"	40-200 N·m	1 N·m	30-150 ft·lb	500	1300	1 / 12	34462-1DK
34466-3FG	32	1/2"	60-300 N·m	1 N·m	45-220 ft·lb	633	1470	1 / 12	34462-1DK

3/4" 34666

KT NO.	Gear teeth	Square drive	Torque range N·m	Incr.	Torque range ft·lb	Overall length mm			DK
34666-1FG	24	3/4"	100~600 N·m	2 N·m	75~440 ft·lb	1040	4650	1 / 2	34666-1DK
34666-2FG	24	3/4"	150~800 N·m	2 N·m	110~590 ft·lb	1235	5450	1 / 2	34666-1DK
34666-3FG	24	3/4"	200~1000 N·m	2 N·m	150~740 ft·lb	1238	5450	1 / 2	34666-3DK