

Slogging Wrench




CAUTION Please wear proper safety gear while working.




10A0

- Open end slogging
- Finished with phosphate sunk
- DIN 133



10B0

- Ring slogging
- Finished with phosphate sunk
- DIN 7444



KT NO.	Size mm	L mm	D mm	H mm		
10A0-24	24	178	52	15	286	6 / 72
10A0-27	27	180	55	16	339	6 / 72
10A0-30	30	190	60	16	416	6 / 60
10A0-32	32	190	61	17	401	6 / 60
10A0-36	36	215	72	17	573	6 / 24
10A0-41	41	233	83	19	855	5 / 20
10A0-46	46	255	94	20	1102	4 / 16
10A0-50	50	275	105	22	1502	2 / 16
10A0-55	55	298	115	24	2161	2 / 12
10A0-60	60	320	127	24	2374	1 / 10
10A0-65	65	340	138	27	3204	1 / 8
10A0-70	70	370	156	32	3785	1 / 5
10A0-75	75	372	153	31	3715	1 / 5
10A0-80	80	395	175	33	6820	1 / 4
10A0-85	85	395	175	33	6300	1 / 4
10A0-90	90	440	197	38	9270	1 / 2
10A0-95	95	440	197	38	8700	1 / 2
10A0-A0	100	480	230	45	10500	1 / 2
10A0-A5	105	480	230	45	10300	1 / 2
10A0-B0	110	505	238	47	14420	1 / 1
10A0-B5	115	505	250	53	14420	1 / 1
10A0-C0	120	530	258	53	15450	1 / 1
10A0-C5	125	530	258	56	15015	1 / 1

KT NO.	Size mm	L mm	D mm	H mm		
New 10B0-17	17	147	33	13	158	6 / 72
New 10B0-19	19	147	33	13	143	6 / 72
New 10B0-21D1	21	156	38.5	13	216	6 / 72
New 10B0-22D1	22	156	38.5	13	195	6 / 72
10B0-24	24	162	42	16	238	6 / 72
10B0-26	26	180	46	17	341	6 / 72
10B0-27	27	180	46	17	330	6 / 72
10B0-30	30	190	52	18	431	6 / 72
10B0-32	32	190	52	18	404	6 / 60
10B0-34	34	195	56	13	471	6 / 36
10B0-36	36	205	58	19	534	6 / 36
10B0-41	41	230	66	21	728	6 / 24
10B0-46	46	240	74	23	877	4 / 16
10B0-50	50	250	82	23	1085	4 / 16
10B0-55	55	265	88	24	1429	2 / 16
10B0-60	60	275	95	26	1644	2 / 12
10B0-65	65	295	104	28	1875	2 / 12
10B0-70	70	325	112	33	2965	1 / 8
10B0-75	75	325	115	33	2735	1 / 8
10B0-80	80	345	128	36	3675	1 / 6
10B0-85	85	345	130	36	3710	1 / 6
10B0-90	90	380	152	40	5850	1 / 4
10B0-95	95	380	152	40	5350	1 / 4
10B0-A0	100	410	161	43	6445	1 / 4
10B0-A5	105	415	172	45	6500	1 / 3
10B0-B0	110	440	172	47	8000	1 / 3
10B0-B5	115	440	172	47	7500	1 / 3
10B0-C0	120	470	194	53	9000	1 / 2


Brake Caliper Slogging Wrench

New

10B0B



- Use for the assembly and removal of the brake caliper screw connections on commercial vehicles
- Designed with a 3/4" DR., can be used with torque wrenches for tightening operations
- The torque adjustment formula laser etched onto the wrench for calculating the correct setting torque when tightening the fixings



KT NO.	Size mm	Application	L mm		
10B0B-24	M24	SAF	215	580	1 / 24
10B0B-26	M26	DAF XF, XF95, XF105, XF106	220	580	1 / 24
10B0B-E18	E18	MAN TGL, TGM	215	580	1 / 24
10B0B-E20	E20	MAN TGL, TGM	215	580	1 / 24
10B0B-E24	E24	MAN TGA, TGS, TGX	220	580	1 / 24

