


T-type Universal Standard Socket Wrench

5774M

- T-type 90° universal standard socket wrench
- 2 PC. sliding handle for easy storage



KT NO.	Size mm	l mm	L mm		
577407M	7	200	390	420	10 / 30
577408M	8	200	390	420	10 / 30
577410M	10	200	500	480	10 / 30
577412M	12	200	500	480	10 / 30
577413M	13	200	500	480	10 / 30
577414M	14	200	500	500	10 / 30
577417M	17	200	500	500	10 / 30
577419M	19	200	500	500	10 / 30



T-shaped Driver

- Chrome vanadium alloy steel
- Chrome plated

3511

3/8"

- Chrome vanadium alloy steel



KT NO.	l mm	L mm		
3511-06	170	268	324	5 / 30
3511-10	250	268	383	6 / 30

T-shaped Driver

- Chrome vanadium alloy steel
- Chrome plated

4795

1/2"

- T-type 90° universal joint driver
- Chrome vanadium alloy steel





KT NO.	l mm	L mm		
4795-18	200	460	567	10 / 30

4511

1/2"

- Chrome vanadium alloy steel




KT NO.	l mm	L mm		
4511-06	170	268	396	5 / 30
4511-10	250	268	463	6 / 30

21A107



- Applied with power bit



KT NO.	Size inch	l mm	L mm		
21A107	1/4	150	175	194	10 / 60