

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted

1600E

- For torx Plus head screw
- 36 / 80mmL



1636xxE



1680xxE

KT NO.	Size	Overall length (mm)	g	set / box
163610E	IP10	36	15	12 / 144
163615E	IP15	36	16	12 / 144
163620E	IP20	36	16	12 / 144
163625E	IP25	36	16	12 / 144
163627E	IP27	36	17	12 / 144
163630E	IP30	36	17	12 / 144
163640E	IP40	36	18	12 / 144
163645E	IP45	36	20	12 / 144
163650E	IP50	36	21	12 / 144
163655E	IP55	36	25	12 / 144
163660E	IP60	36	31	12 / 120
168010E	IP10	80	45	6 / 72
168015E	IP15	80	45	6 / 72
168020E	IP20	80	45	6 / 72
168025E	IP25	80	46	6 / 72
168027E	IP27	80	46	6 / 72
168030E	IP30	80	47	6 / 72
168040E	IP40	80	48	6 / 72
168045E	IP45	80	49	6 / 72
168050E	IP50	80	50	6 / 72
168055E	IP55	80	60	6 / 72
168060E	IP60	80	79	6 / 60

1600M

- 36 / 80mmL



1636xxM



1680xxM

KT NO.	Size	Overall length (mm)	g	set / box
163605M	M5	36	18	12 / 144
163606M	M6	36	19	12 / 144
163608M	M8	36	20	12 / 144
163609M	M9	36	21	12 / 144
163610M	M10	36	22	12 / 144
163612M	M12	36	28	12 / 120
163614M	M14	36	30	12 / 120
168005M	M5	80	47	6 / 72
168006M	M6	80	48	6 / 72
168008M	M8	80	49	6 / 72
168009M	M9	80	51	6 / 72
168010M	M10	80	52	6 / 72
168012M	M12	80	70	6 / 60
168014M	M14	80	71	6 / 60

10mm Hex size shank driver



order unit : one blister card

1600U

- For torx head screw
- Tamper-resistant type
- 36 / 80mmL



1636xxU



1680xxU

KT NO.	Size	Overall length (mm)	g	set / box
163610U	T10H	36	17	12 / 144
163615U	T15H	36	17	12 / 144
163620U	T20H	36	18	12 / 144
163625U	T25H	36	18	12 / 144
163627U	T27H	36	18	12 / 144
163630U	T30H	36	18	12 / 144
163640U	T40H	36	20	12 / 144
163645U	T45H	36	21	12 / 144
163650U	T50H	36	23	12 / 144
163655U	T55H	36	28	12 / 144
163660U	T60H	36	33	12 / 120
168010U	T10H	80	46	6 / 72
168015U	T15H	80	47	6 / 72
168020U	T20H	80	47	6 / 72
168025U	T25H	80	47	6 / 72
168027U	T27H	80	47	6 / 72
168030U	T30H	80	47	6 / 72
168040U	T40H	80	48	6 / 72
168045U	T45H	80	49	6 / 72
168050U	T50H	80	50	6 / 72
168055U	T55H	80	52	6 / 72
168060U	T60H	80	70	6 / 60

