



## Soldering Iron Tip (Conical Type)

### 6BC23-1


- Copper-based iron tips are manufactured using patented process which produces a uniform iron and chrome plating thickness

KT NO.	Rating W	Ø mm		
6BC23-1	30 / 40	4	13	100 / 4200
6BC26-1	60	6	16	100 / 1600
6BC26-3	60	6	16	100 / 1600

### 6BC26-1

### 6BC26-3

- All tips are pre-tinned













## 3 in 1 Gas Soldering Iron Set


### 6BC3007

- Gas soldering iron set with four tips, reflector and desolder wire
- Power range: 30W-150W
- Soldering temperature: 400° C~450° C (750° F~840° F)
- Torch temperature: 1300° C (2400° F)
- Fuel capacity: 20ml
- Tank fuel for 90 minutes operation
- Ready to use 45 seconds after ignition



8  
PC.

KT NO.	Contents	 0.45	
6BC372		Gas soldering iron 257mm	
6BC372-1		Conical	
6BC372-2		2.5mm round	
6BC372-3		3.5mm chisel	
6BC372-4		4.5mm angle	
6BC372-5		Reflector	
6BF21-17		Desolder wire / Sn 99.3%, Cu 0.7%	
		Foam	





## Soldering Wire

### 6BF11-17

- 40% lead and 60% tin





KT NO.	Size mm		
6BF11-17	1.0	27	20 / 480

## Desoldering Pump

### 6BD11

- One-hand operation
- ABS Body, teflon nozzle



KT NO.	Overall length mm		
6BD11	195	42	8 / 32

### 6BD22

- Anti-static solder desoldering pump
- Teflon suction head
- Aluminum body





- Turn down the body



- Turn up the body

- Clean

KT NO.	Overall length mm		
6BD22	197	85	50 / 100