

# Marking Punch



CAUTION Please wear proper safety gear while working.



## 11409SQ

- Chrome vanadium alloy steel
- Hardened and tempered control HRC60 for safe use
- Invert number 6 to be number 9 (For 11409SQ)
- The letter A~Z with extra "&" (ampersand) included (For 11427SQ)



The position hole help to fix the marking punch

11409SQ

## 11427SQ



11427SQ

| KT NO.    | Font size<br>mm | inch  | Contents         | Shank<br>mm <sup>2</sup> | L<br>mm | Kg   | Box / Carton |
|-----------|-----------------|-------|------------------|--------------------------|---------|------|--------------|
| 11409SQ02 | 2.0             | 5/64" | 9 PCS<br>0~9     | 6.35                     | 61      | 0.18 | 1 / 80       |
| 11409SQ03 | 3.0             | 1/8"  |                  | 6.35                     | 61      | 0.18 | 1 / 80       |
| 11409SQ04 | 4.0             | 5/32" |                  | 6.35                     | 59      | 0.18 | 1 / 80       |
| 11409SQ05 | 5.0             | 3/16" |                  | 8                        | 61      | 0.28 | 1 / 50       |
| 11409SQ06 | 6.0             | 1/4"  |                  | 9.53                     | 61      | 0.43 | 1 / 36       |
| 11409SQ08 | 8.0             | 5/16" |                  | 12.7                     | 71      | 0.78 | 1 / 18       |
| 11427SQ02 | 2.0             | 5/64" | 27 PCS<br>A~Z, & | 6.35                     | 61      | 0.52 | 1 / 30       |
| 11427SQ03 | 3.0             | 1/8"  |                  | 6.35                     | 61      | 0.52 | 1 / 30       |
| 11427SQ04 | 4.0             | 5/32" |                  | 6.35                     | 59      | 0.52 | 1 / 30       |
| 11427SQ05 | 5.0             | 3/16" |                  | 8                        | 61      | 0.82 | 1 / 16       |
| 11427SQ06 | 6.0             | 1/4"  |                  | 9.53                     | 61      | 1.25 | 1 / 12       |
| 11427SQ08 | 8.0             | 5/16" |                  | 12.7                     | 71      | 2.33 | 1 / 6        |

# Heavy Duty Marking Punch

## 11509SQ

- Chrome vanadium alloy steel
- Hardened and tempered control HRC60 for safe use
- Hardness reduced at striking end HRC40 to have longer life time
- Invert number 6 to be number 9 (For 11509SQ)
- The letter A~Z with extra "&" (ampersand) included (For 11527SQ)



11509SQ05

## 11527SQ



11527SQ05

| KT NO.    | Font size<br>mm | inch  | Contents         | Shank<br>mm <sup>2</sup> | L<br>mm | Kg   | Box / Carton |
|-----------|-----------------|-------|------------------|--------------------------|---------|------|--------------|
| 11509SQ05 | 5.0             | 3/16" | 9 PCS<br>0~9     | 11                       | 61      | 0.56 | 1 / 30       |
| 11527SQ05 | 5.0             | 3/16" | 27 PCS<br>A~Z, & | 11                       | 61      | 1.70 | 1 / 10       |

