

# Figure Tin Snips

## 74250~74270

- Special drop forged CRMO with induction hardened edges 63HRC
- Blades with serrated edges fast cuts in sheet metal, aluminum, and much more
- Cut 1.5mm cold-rolled steel (16GA) low carbon steel
- Non-slip color code grips for superior control
- Special laborsaving design
- High tensile strength provided
- High torsional strength spring designed
- Solid and comfortable handle with non-slip design
- Hang-up hole for convenient storage
- Safety auto latch (D.PAT.)





74250



74260



74270

| KT NO. | Overall length<br>mm | Cutting length<br>mm | Color of handle | Copper (soft) | Cutting capacities (mm)  |                          |                    |  |  |
|--------|----------------------|----------------------|-----------------|---------------|--------------------------|--------------------------|--------------------|---|---|
|        |                      |                      |                 |               | Cold-rolled steel (soft) | Hard steel HRC 30 (Hard) | Stainless steel304 |   |   |
| 74250  | 260                  | 35                   | Orange          | 1.80          | 1.50                     | 1.00                     | 0.90               | 480   | 6 / 36  |
| 74260  | 260                  | 35                   | Blue            | 1.80          | 1.50                     | 1.00                     | 0.90               | 480   | 6 / 36  |
| 74270  | 260                  | 35                   | Yellow          | 1.80          | 1.50                     | 1.00                     | 0.90               | 480   | 6 / 36  |



# Straight Pattern Snips

## 74410~74416

- Drop forged of finest quality steel induction hardened edges 60HRC
- Cuts straight flat face guides tool along straight line
- Blades individually hand edged for maximum cutting efficiency
- Cushion handle for comfort and better grip



74410 ~ 74416

| KT NO. | Overall length<br>mm | Cutting length<br>mm | Copper<br>(soft) | Cutting capacities (mm)     |                             |      | Stainless<br>steel304 |  |  |
|--------|----------------------|----------------------|------------------|-----------------------------|-----------------------------|------|-----------------------|---|---|
|        |                      |                      |                  | Cold-rolled Steel<br>(soft) | Hard steel<br>HRC 30 (Hard) |      |                       |   |   |
| 74410  | 254                  | 51                   | 0.94             | 0.78                        | 0.60                        | 0.45 | 480                   | 6 / 36  |   |
| 74412  | 305                  | 70                   | 1.15             | 0.91                        | 0.70                        | 0.63 | 650                   | 6 / 24  |   |
| 74414  | 356                  | 76                   | 1.41             | 1.20                        | 1.00                        | 0.70 | 780                   | 6 / 24  |   |
| 74416  | 415                  | 63                   | 2.00             | 1.60                        | 1.20                        | 1.00 | 1700                  | 3 / 12  |   |

# Curved Tin Snips



## 74512

- Drop forged of finest quality steel induction hardened edges 60HRC
- Double curved, hollow ground blades reduce friction for easier cutting
- British Gilbow type
- Cushion handle for comfort and better grip

## 74514



74512 / 74514

| KT NO. | Overall length<br>mm | Cutting length<br>mm | Copper<br>(soft) | Cutting capacities (mm)     |                             |                       |  |  |
|--------|----------------------|----------------------|------------------|-----------------------------|-----------------------------|-----------------------|---|---|
|        |                      |                      |                  | Cold-rolled steel<br>(soft) | Hard steel<br>HRC 30 (Hard) | Stainless<br>steel304 |   |   |
| 74512  | 305                  | 60                   | 1.15             | 0.91                        | 0.70                        | 0.63                  | 670   | 6 / 24  |
| 74514  | 356                  | 65                   | 1.40             | 1.20                        | 1.00                        | 0.70                  | 920   | 6 / 24  |