




## Three-Legs Oil Filter Wrench

### 9AE42

- The claw-type filter is available for removing all oil filters from 2-1/2" to 4" (63-102mm) in diameter
- Suitable for 3/8" or 1/2" square drive tool
- Coated with electro-black oxide finish for protection against rust
- CW & CCW direction**


KT NO.	A inch	B inch	inch	Ø Capacity mm		
9AE42	1/2	3/8	2-1/4~4	63~102	395	12 / 48
9AE221	1/2	3/8	-	-	39	-
9AE433	1/2	3/8	2-9/16~4-23/32	65~120	502	12 / 36



### 9AE43

- The claw-type filter is available for removing all oil filters from 3" to 4-3/4" (75-120mm) in diameter
- Suitable for 3/8" or 1/2" square drive tool
- Heavy duty design
- CW & CCW direction**



KT NO.	A inch	B inch	inch	Ø Capacity mm		
9AE43	1/2	3/8	3~4-3/4	75~120	604	1 / 36




## Two Jaws Oil Filter Wrench

### 9AE52

- The two jaws oil filter wrench is capable of removing all kinds of oil filter
- Suitable for using with 1/2" square drive tool
- Lost wax coating with electro-black oxide finish for protection against rust
- Specially teeth designed steel jaws

KT NO.	A inch	inch	Ø Capacity mm		
9AE52	1/2	2-3/8~3-1/8	60~80	470	1 / 16
9AE52-110	1/2	3-1/8~4-5/16	80~110	985	1 / 12



### 9AE53

- The claw-type filter is available for removing all oil filters from 3-1/8" to 4-1/2" (80-115mm) in diameter
- Suitable for using with 1/2" square drive tool
- Coated with electro-black oxide finish for protection against rust

KT NO.	A inch	inch	Ø Capacity mm		
9AE53-115	1/2	3-1/8~4-1/2	80~115	667	6 / 24

