

Pneumatic Grease Pump 20L

9TU10-20

- The barrel body is made of high-grade steel plate. It can contain 5 gallons(20L) of barrel packed grease
- Suitable #00,#0,#1,#2 grease oil for all sorts of machinery, Heavy goods vehicles, airplanes, ships, etc. for lubrication & maintenance purpose
- The follower plate can prevent air pockets from forming and possible cavitation of the pump and enable to collect all the grease from the bottom of the drum and keep it clean
- Pump of separate type: utilize the principle of liquid getting pumped & driven by air compressor to draw in liquid. There are two independent & separate cycle systems of pump out there, which prevents air-compressor-exhaust moisture from getting to the grease inside the barrel and deteriorating its quality



| KT NO. | Air Input (bar) | Pressure (PSI) | Pressure Ratio | Grease (bar) | Output Pressure (PSI) | Deliver Rate (cc/sec) | N.W. | G.W. | kg | CUFT |
|----------|-----------------|----------------|----------------|--------------|-----------------------|-----------------------|------|------|------|------|
| 9TU10-20 | 4-9 | 60-130 | 45 : 1 | 180-405 | 2700-5850 | 30 | 17 | 20.5 | 21.0 | 6.4 |

Hand Grease Pump 20/30L

9TU21

- Suitable for #00,#0,#1,#2 grease oil
- Included 1.8m length hose & pistol sprayer
- 1/4" High pressure 10,000 psi W.P oilfield hose
- Portable equipment with single pull handle
- Suitable for all sorts of machinery, Heavy goods vehicle, airplanes, ships, etc.



| KT NO. | Capacity | Transmission Rate | Hose Length | N.W. | G.W. | CUFT |
|----------|----------|-------------------|-------------|---------|---------|------|
| 9TU21-20 | 20 L | 4 cc/stroke | 1.8 m | 8.2 Kg | 9.4 Kg | 2.2 |
| 9TU21-30 | 30 L | 4 cc/stroke | 1.8 m | 10.5 Kg | 12.6 Kg | 5.1 |

Oil Transfer Bucket Pump 20L

9TW21

- Lever pump 20 L tank for oil
- Suitable for diesel fuel, lubricating oils up to SAE 90 and Non-corrosive fluids
- Included 1.8m length hose & sprayer
- Portable equipment with single pull handle



| KT NO. | Deliver Rate | Hose Length | Outlet Tube | N.W. | G.W. | CUFT |
|----------|--------------|-------------|-------------|--------|-------|------|
| 9TU21-22 | 65 cc/stroke | 1.8m | 3/8" | 7.8 Kg | 8.5Kg | 2.2 |