


Impact Torsion Bit

- Silicon chrome vanadium alloy steel(S2)
- Anti-rust oiled, electroplating



30x ↑

Torsion zone

- Absorbs high impact stress
- Enhance the torsion effect
- Reducing Bit breakage
- Achieve up to a 30X increase in lifespan

- 2 PC. bits set
- Color code

1/4" Hex size shank driver

order unit : one blister card

7T50T



- For torx head screw



KT NO.	Size	Overall length (mm)	g	set / box
7T5010T-S1	T10	50	16	20 / 160
7T5015T-S1	T15	50	16	
7T5020T-S1	T20	50	18	
7T5025T-S1	T25	50	18	
7T5027T-S1	T27	50	20	
7T5030T-S1	T30	50	20	
7T5040T-S1	T40	50	22	

7T50P



- Short neck (9.5 mm) type
- DIN ISO 2351-2



KT NO.	No.	Overall length (mm)	g	set / box
7T5001P-S1	PH1	50	18	20 / 160
7T5002P-S1	PH2	50	18	
7T5003P-S1	PH3	50	20	

7T50S



- DIN ISO 2351-1



KT NO.	Tip width (mm)	Tip thickness (mm)	Overall length (mm)	g	set / box
7T5003S1-S	3.0	0.5	50	16	20 / 160
7T5004S1-S	4.0	0.5	50	16	
7T5005S1-S	5.0	0.8	50	20	
7T5006S1-S	6.0	1.0	50	20	

7T50Z



- DIN ISO 2351-2



KT NO.	No.	Overall length (mm)	g	set / box
7T5001Z-S1	PZ1	50	18	20 / 160
7T5002Z-S1	PZ2	50	18	
7T5003Z-S1	PZ3	50	20	

7T50H



- DIN ISO 2351-3



KT NO.	mm	Overall length (mm)	g	set / box
7T5003H-S1	H3	50	18	20 / 160
7T5004H-S1	H4	50	18	
7T5005H-S1	H5	50	22	
7T5006H-S1	H6	50	24	

NEW

KING TONY